

PENTAX

Positioning Systems Model

Precision Satellite Surveying
with Wireless Communications

G7N

GPS | GLONASS | BEIDOU | SBAS | GALILEO



- + Compact and durable metal housing
- + Better dust and weather resistance (IP67)
- + Equipped with calibration free IMU sensor that compensates tilting of the receiver
- + WiFi for direct communication with web browser for e.g. downloading data, firmware upgrades and communication between receiver and controller

TI Asahi Co.,Ltd
Focusing on true performance

GNSS SPECIFICATIONS

Model	G7N	
Channel Configuration		555 channels
		Multi-Frequency GPS, GLONASS, Galileo, Beidou, IRNSS*1 and QZSS
Receiver Board		NovAtel 719
Signal Tracking	GPS	L1 C/A, L1P, L1C, L2P, L2C, L5
	GLONASS	L1 C/A, L2C, L2P, L3, L5
	BEIDOU	B1, B2, B3
	Galileo	E1, E5 AltBOC, E5a, E5b, E6
	QZSS	L1 C/A, L1C, L2C, L5, L6
	SBAS	L1, L5
	NavIC (IRNSS) *1	L5
	L-Band	up to 5 channels
Position Accuracy	SBAS (WAAS, GAGAN etc.)	0.5 m
	DGPS	0.4 m
RTK Performance	Horizontal Accuracy	8 mm + 1 ppm
	Vertical Accuracy	15 mm + 1 ppm
	Horizontal Accuracy (Network RTK)	8 mm + 0.5 ppm
	Vertical Accuracy (Network RTK)	15 mm + 0.5 ppm
	Average Time to Work	Typ. < 10 sec.
	Availability/Initialization Reliability	> 99.9%
Static Performance	Horizontal Accuracy(Long time observation) *2	3 mm + 0.1 ppm
	Vertical Accuracy(Long time observation) *2	3.5 mm + 0.4 ppm
	Horizontal Accuracy	2.5 mm + 0.5 ppm
	Vertical Accuracy	5 mm + 0.5 ppm
PPP (Precision Point Positioning)		Horizontal 40mm with TerraStar C (optional)
Ports		Lemo 5-pin, external radio and power supply
		Lemo 7-pin, serial port and USB
Internal Radio Modem	Frequency	410 Mhz - 470 Mhz
	Output Power	0.5 W / 1 W
Cell Modem	Modem	Worldwide LTE
	Frequency Bands	UMTS/HSPA+/GSM/GPRS/EDGE
	Network Protocol	NTRIP, HTTP, FTP
Power	Internal Battery	3,350 mAh / 7.4 V x2
	Current Drain	0.35 A / 12 V
		1.25 A / 12 V max.
	Battery Running Time	Approx. 12 hr: Rover, 10 hr: Base with 2 Batteries
Weight		1.1 kg with 2 batteries
Dimensions		Ø 130 mm x H 100 mm
Environmental Specifications	Operating Temperature	-30 °C to +65 °C
	Storage Temperature	-30 °C to +65 °C
	Shock/Drop	2 m
Velocity Accuracy	Standalone	0.03 m/sec RMS
Data Output	Raw Data output frequency	5 Hz (20 Hz optional)
	NMEA Data output frequency	5 Hz (20 Hz optional)
	Correction data Protocol	RTCM Ver 2.1, 2.2, 2.3, 3.0, 3.1, 3.2 CMR, CMR+, sCMRx
Time to First Fix	Cold Start	< 50 sec
	Warm Start	< 35 sec
	Reacquisition	< 1 sec
WiFi		IEEE 802.11b/g
IMU	Electric Bubble	Yes
	Tilt compensated	Tilt range up to 60°
	Tilt accuracy	10 mm + 0.4 mm/° (up to 30°)
	Reliability	Magnetism interference free
Bluetooth		Class 2
Memory		Internal 8 GB and MicroSD 8 GB
RoHS		Complied
Waterproofing		IP67
Certification		CE
Standard Accessories		2 x Li-Ion rechargeable battery pack
		Battery charger + AC Adapter
		5/8 inch screw adapter
		Lemo 7-pin communication cable
		CD (contains manual and data conversion software)

*1 Hardware ready

*2 Performance, Accuracy and Reliability are dependent upon various factors including satellite geometry, number of satellites, ionospheric conditions, atmospheric conditions and multipath.

PENTAX Positioning System is dedicated to providing customers with first class positioning system products and freedom of choice. We have carefully designed high-quality products to meet the needs of today's surveyors based on the experience of many years involved in instrument design and construction. Our engineers have been involved in Survey products since the beginning of the Satellite Surveying Era. We are committed to ease of use, a low cost of ownership and flexibility to accommodate different working environments. Our close partners are carefully chosen and are committed to these values as we are.

www.pentaxsurveying.com/en/

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

Your Official Pentax Dealer

AGP SERVISS



ISO 9001:2015 Certified



The CE marking assures that this product complies with the requirements of the EC directive for safety.

JSIMA
 Japan Surveying Instruments Manufacturers' Association

Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.